

Product technical sheet

SOLO WP2863







1+

20 kids

26,5 m²

Material specification

- Stainless steel construction,
- Gutter, tanks made of stainless steel, protected from the top with transparent polycarbonate,
- Gutter barriers made of rubber, HDPE and stainless steel,
- Manipulative elements made of stainless steel and HDPE,
- Plugs for gutters and tanks made of stainless steel and plastic,
- Tap made of surgical stainless steel AISI 316, intended for connection to the public water supply network,
- Stainless steel screws and/or screws covered with plastic caps,




Facilitating disability



easy access





Product technical sheet

SOLO WP2863

Product data

Length	325 cm	
Width	250 cm	
Total height	125 cm	
Age group	1+ years	
Number of users	20 kids	
Safety zone	26,5 m2	
Free fall height	< 60 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	14,6 kg	
Availability of spare parts	YES	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
hark (A.C.)	Particle size from 20 to 80	30	≤200
Dark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		< 60

Product technical sheet

SOLO WP2863

Amount of safe surface corresponding with free fall height:

HIC <60 26,5 m²

Data is subject to change without prior notice.

