
Win play

Product technical sheet

JUMPOO 2213






Material specification

- Construction made of hot-dip galvanised steel, mounted below the ground surface,
- The edges of the structure covered with a rubber rim surface colored SBR glued to the frame,
- Jumping mat: made of polyamide lamellas, threaded on a stainless steel rope,
- Fastening on durable galvanized springs inside the structure,



Win play





Product technical sheet JUMPOO 2213

Product data

Length	200 cm
Width	200 cm
Age group	4 - 15 years
Number of users	1 kids
Safety zone	34,1 m2
Free fall height	90 cm
In accordance with norm EN	1176-1:2017
Availability of spare parts	YES
Color options	

Data is subject to change without prior notice.

Additional information


- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components

Detailed information in the guarantee card



tee tee of steel teel, for ment pr

10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Partic	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	Particle size from 5	30	≤200
	40	≤300	
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		90

Product technical sheet

JUMPOO 2213

Amount of safe surface corresponding with free fall height:

HIC 90	34,1 m²
--------	---------

Data is subject to change without prior notice.

