

Product technical sheet

SWING ST0525







3 - 14 years

4 kids

12,9 m²





Material specification

- Stainless steel and hot-dip galvanized and powder coated steel construction,
- Seats made of durable HDPE plate, resistant to weather conditions,
- Handles made of stainless steel,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,



Physical development




community



rocking

Tel: +48 221 530 191 Email: info@playground.com.pl





06



Product technical sheet

SWING ST0525

Product data

Length	375 cm	
Width	40 cm	
Total height	90 cm	
Age group	3 - 14 years	
Number of users	4 kids	
Safety zone	12,9 m2	
Free fall height	99 cm	
In accordance with norm EN	1176-1:2017	
Availability of spare parts YES		

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A.C.)	30 Particle size from 20	30	≤200
bark (A,C)	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	Particle size from 5	30	≤200
	to 30	40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		99

Product technical sheet

SWING ST0525

Amount of safe surface corresponding with free fall height:

HIC 99 12,9 m²

Data is subject to change without prior notice.

